

## DATA SHEET

### BH-102

Description: 2 ply European belt, fabric bottom, smooth PVC top

Applications: General Conveying

Features: Anti-static, medium friction top cover, monofilament carcass

Technical Data:

Overall Thickness: 0.11 inches / 2.8 mm

Minimum Pulley Diameter: 2.0 inches / 50 mm

Pull for 1% Elongation: 74.0 lbs per inch / 12.9 N per mm

Maximum Admissible Strength: 74.0 lbs per inch / 12.9 N per mm

Coefficient of Friction vs Kraft Board - Cover: 0.8  $\mu$

Color: Green

Maximum Width: 118 inches / 3000 mm

Recommended Joining Methods: Finger Splice, Clipper or Alligator Lacing



CONVEYING SURFACE

BELT DIRECTION  
OF TRAVEL



PULLEY SIDE

**BOWMAN HOLLIS MFG.**  
[WWW.BOWMANHOLLIS.COM](http://WWW.BOWMANHOLLIS.COM)

**NORTH CAROLINA**  
2925 OLD STEELE CREEK ROAD  
CHARLOTTE, NC 28208  
TOLL FREE: 888-269-2358  
LOCAL: 704-374-1500  
FAX: 704-333-5520

**GEORGIA**  
1606 ORCHARD HILL RD  
LaGRANGE, GA 30240  
TOLL FREE: 800-822-64838  
LOCAL: 706-882-6483  
FAX: 706-882-7697