

## DATA SHEET

### BH-108

Description: 2 ply European belt, smooth white PVC both top and bottom sides

Applications: Corrugated box industry: understackers and counter ejectors.

Additional Applications: Many uses in general board conveying where good friction is needed

Features: Strong, stretch free construction. Intermediate friction PVC on both sides.

#### Technical Data:

Overall Thickness: 0.16 inches / 4.1 mm

Minimum Pulley Diameter - Spliced Belt: 5.5 inches / 140 mm

Minimum Pulley Diameter - Laced Belt: 3.5 inches / 90 mm

Pull for 1% Elongation: 114.2 lbs per inch / 20.0 N per mm

Tensile (breaking) Strength: 1142 lbs per inch / 200 N per mm

Coefficient of Friction vs Kraft Board - Cover and Pulley Side: 0.5  $\mu$

Color: White

Maximum Width: 78 inches / 2000 mm

Recommended Joining Methods: Finger Splice, Clipper or Alligator Lacing



CONVEYING SURFACE

BELT DIRECTION  
OF TRAVEL



PULLEY SIDE

**BOWMAN HOLLIS MFG.**  
[WWW.BOWMANHOLLIS.COM](http://WWW.BOWMANHOLLIS.COM)

**NORTH CAROLINA**  
2925 OLD STEELE CREEK ROAD  
CHARLOTTE, NC 28208  
TOLL FREE: 888-269-2358  
LOCAL: 704-374-1500  
FAX: 704-333-5520

**GEORGIA**  
1606 ORCHARD HILL RD  
LaGRANGE, GA 30240  
TOLL FREE: 800-822-64838  
LOCAL: 706-882-6483  
FAX: 706-882-7697