

DATA SHEET

BH-109

Description: 2 ply European belt, fabric top and bottom

Applications: Food conveying, general conveying where white belt and structure is desired.

Features: Anti-static, FDA compliant, monofilament carcass.

Technical Data:

Overall Thickness: 0.06 inches / 1.6 mm

Minimum Pulley Diameter: 0.8 inches / 20 mm

Pull for 1% Elongation: 46.0 lbs per inch / 8.0 N per mm

Maximum Admissible Strength: 46.0 lbs per inch / 8.0 N per mm

Coefficient of Friction vs Kraft Board - Cover: 0.3 μ

Color: White

Maximum Width: 118 inches / 3000 mm

Recommended Joining Methods: Finger Splice, Clipper or Alligator Lacing



CONVEYING SURFACE

BELT DIRECTION
OF TRAVEL



PULLEY SIDE

BOWMAN HOLLIS MFG.
WWW.BOWMANHOLLIS.COM

NORTH CAROLINA
2925 OLD STEELE CREEK ROAD
CHARLOTTE, NC 28208
TOLL FREE: 888-269-2358
LOCAL: 704-374-1500
FAX: 704-333-5520

GEORGIA
1606 ORCHARD HILL RD
LaGRANGE, GA 30240
TOLL FREE: 800-822-64838
LOCAL: 706-882-6483
FAX: 706-882-7697