

## DATA SHEET

### BH-119

Description: Interwoven domestic belt, brushed by friction

Applications: General conveying distribution center belt

Features: Brushed pulley side, low friction top side

Technical Data:

Overall Thickness: 0.125 inches / 3.2 mm

Minimum Pulley Diameter: 3.1 inches / 80 mm

Pull for 1% Elongation: 120.0 lbs per inch / 21.0 N per mm

Maximum Admissible Strength: 127 lbs per inch / 24 N per mm

Coefficient of Friction vs Kraft Board - Cover: 0.4  $\mu$

Color: Black

Maximum Width: 72 inches / 1830 mm

Recommended Joining Methods: Clipper or Alligator Lacing.



CONVEYING SURFACE

BELT DIRECTION  
OF TRAVEL



PULLEY SIDE

**BOWMAN HOLLIS MFG.**  
[WWW.BOWMANHOLLIS.COM](http://WWW.BOWMANHOLLIS.COM)

**NORTH CAROLINA**  
2925 OLD STEELE CREEK ROAD  
CHARLOTTE, NC 28208  
TOLL FREE: 888-269-2358  
LOCAL: 704-374-1500  
FAX: 704-333-5520

**GEORGIA**  
1606 ORCHARD HILL RD  
LaGRANGE, GA 30240  
TOLL FREE: 800-822-64838  
LOCAL: 706-882-6483  
FAX: 706-882-7697