

DATA SHEET

BH-122

Description: 4 ply cotton/nylon fabric bonded with tan SBR rubber

Applications: General industrial use, power transmission belt

Features: 4 ply

Technical Data:

Overall Thickness: 0.17 inches / 4.3 mm

Minimum Pulley Diameter: 3.0 inches / 76 mm

Pull for 1% Elongation: 120.0 lbs per inch / 21.5 N per mm

Tensile (breaking) Strength: 1200 lbs per inch / 215 N per mm

Coefficient of Friction vs Kraft Board - Cover: 0.4 μ

Color: Tan

Maximum Width: 72 inches / 1830 mm

Recommended Joining Methods: Clipper or Alligator Lacing.



CONVEYING SURFACE

BELT DIRECTION
OF TRAVEL



PULLEY SIDE

BOWMAN HOLLIS MFG.
WWW.BOWMANHOLLIS.COM

NORTH CAROLINA
2925 OLD STEELE CREEK ROAD
CHARLOTTE, NC 28208
TOLL FREE: 888-269-2358
LOCAL: 704-374-1500
FAX: 704-333-5520

GEORGIA
1606 ORCHARD HILL RD
LaGRANGE, GA 30240
TOLL FREE: 800-822-64838
LOCAL: 706-882-6483
FAX: 706-882-7697