

## SPIKED APRON SPECIFICATION SHEET

NAME OF MACHINE APRON OPERATES ON: \_\_\_\_\_

SLAT SHAPE FROM LIST AT BOTTOM (i.e. HP, 8W, etc.): \_\_\_\_\_

LENGTH OF APRON: \_\_\_\_\_

(IF EXACT LENGTH UNKNOWN, COMPLETE LINES A - C)

**A** CENTER TO CENTER OF SHAFTS: \_\_\_\_\_

**B** PULLEY DIAMETER: \_\_\_\_\_

**C** PULLEY DIAMETER: \_\_\_\_\_

**D** SPACING OF SLATS EDGE TO EDGE: \_\_\_\_\_ CENTER TO CENTER: \_\_\_\_\_

**E** WIDTH OF APRON OR SLAT LENGTH: \_\_\_\_\_

NUMBER OF BELTS: \_\_\_\_\_ BELT WIDTH: \_\_\_\_\_

OUTSIDE EDGE OF BELTS EXTENDED TO ACT AS CUSHION? YES \_\_\_\_\_ NO \_\_\_\_\_

BELTS OFFSET \_\_\_\_\_ FROM SLAT EDGE

BELTS LACED \_\_\_\_\_ OR SPLICED ENDLESS \_\_\_\_\_

CANVAS OR OTHER BACKING: YES \_\_\_\_\_ NO \_\_\_\_\_

IS CANVAS BONDED (GLUED) TO BACK OF SLAT? YES \_\_\_\_\_ NO \_\_\_\_\_

IF CHAIN APRON:

CHAIN NUMBER: \_\_\_\_\_ # OF CHAINS: \_\_\_\_\_ #LINKS EA. CHAIN: \_\_\_\_\_

**PIN DESCRIPTION:**

PINS SPACED \_\_\_\_\_ INCHES APART IN EACH SLAT

PIN DIAMETER: \_\_\_\_\_ PIN LENGTH: \_\_\_\_\_

(IF PIN LENGTH AND DIAMETER UNKNOWN, SEND OLD PIN)

PINS TO PROJECT \_\_\_\_\_ INCHES ABOVE SURFACE

PINS ARE: CARBON STEEL \_\_\_\_\_ STAINLESS \_\_\_\_\_ OTHER \_\_\_\_\_

PINS EACH SLAT: IN LINE \_\_\_\_\_ STAGGERED \_\_\_\_\_

APRON USED FOR: \_\_\_\_\_

A - E ABOVE:

