

SPECIFICATION: SPIKED APRON

NAME OF MACHINE APRON RUNS ON:
SLAT SHAPE:
LENGTH OF APRON:
(IF EXACT LENGTH UNKNOWN, FILL IN NEXT 3 LINES)
A C TO C OF SHAFTS:
B PULLEY DIAMETER:
C PULLEY DIAMETER:
D SPACING OF SLATS EDGE TO EDGE: CENTER TO CENTER:
E WIDTH OF APRON OR SLAT LENGTH:
NUMBER OF BELTS: BELT WIDTH:
OUTSIDE BELTS EXTENDED TO ACT AS CUSHION: YES NO
BELTS: LACED ENDLESS
CANVAS OR OTHER BACKING: YES NO
IS CANVAS BONDED (GLUED) TO BACK OF SLATS? YES NO
IF CHAIN APRON:
CHAIN NUMBER NUMBER OF CHAINS NUMBER LINKS EACH CHAIN
PIN DESCRIPTION:
PINS ARE SPACED INCHES APART IN EACH SLAT
PIN DIAMETER: PIN LENGTH: (IF PIN LENGTH & DIAMETER ARE UNKNOWN, SEND OLD PIN)
PINS TO PROJECT INCHES ABOVE SURFACE
PINS ARE: CARBON STEEL STAINLESS STEEL OTHER
PINS EACH SLAT: IN LINE STAGGERED
APRON USED FOR:
- FAROVE
A - E ABOVE:
8W 58
74 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
C16P (3/8)
HP 9/16
B G HP 716
11/0